

T66 Compact Track Loader



No matter how extreme your working conditions, the vertical-lift-path Bobcat® T66 compact track loader tackles tough jobs where other equipment can't.

- Increased lifting capabilities
- Powerful hydraulic performance
- Fast cycle times
- Premium comfort

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)

[Download Brochure](#)

T66 Overview

- The 74-hp T66 compact track loader includes a redesigned Bobcat inline engine and direct-drive system, lift arms with cast-steel construction and improved cooling performance.
- The vertical-lift-path T66 delivers powerful hydraulics and breakout forces, fast cycle times and increased lifting capabilities.
- The roomy T66 cab provides a sealed and pressurized environment complete with an available heated air-ride seat, clear-side enclosure, automatic heat and air conditioning, and an innovative display with machine information and performance data

T66 Specifications

T66 Key Specifications	
Rated Operating Capacity (ISO)	2,450 lb
Operating Weight	8927 lb
Ground Pressure (Rubber)	5.9 psi
Auxiliary Std Flow	17.6 gal/min
Auxiliary High Flow	26.9 gal/min
Joystick Control	Optional

Engine	
Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	yes

Performance	
Rated Operating Capacity (ISO)	2,450 lb
Operating Capacity (50% of Tip)	3500 lb
Tipping Load	7000 lb
Operating Weight	8927 lb
Travel Speed	7.2 mph
Travel Speed (2-speed option)	10.2 mph
Ground Pressure (Rubber)	5.9 psi

Capacities	
Fuel Tank	28.3 gal
Hydraulic System	
System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.6 gal/min
Auxiliary High Flow	26.9 gal/min
Dimension	
Length	134.9 in
Length without Attachment	107 in
Length with Standard Bucket	134.9 in
Width	67 in
Width (with bucket)	68 in
Height	80.5 in
Height with Operator Cab	80.5 in
Height to Bucket Hinge Pin	120 in
Reach @ Maximum Height	36.7 in
Turning Radius	81.5 in
Length of track on ground	54.3 in
Track Width	12.6 in
Track Width - Optional	15.7 in
Features	
Joystick Control	Optional
Air Conditioning	Optional
Backup Alarm	Standard
BICS System (Interlock)	Standard
Cab Heater	Optional
Operating Lights	Standard
Suspension Seat	Standard
Two Speed Travel	Optional
Deluxe Instrumentation	Optional
Engine Shutdown	Standard
Hydraulic Bucket Positioning	Optional
High Flow Option	Optional
Auxiliary Hydraulics	Standard
Bob-Tach Attachment System	Standard
Power Bob-Tach	Optional
ACS (Switchable Controls)	Not Applicable
Ride Control	Optional
Horn	Standard
Cab Enclosure	Optional
Adjustable Seat	Standard
Sound Option	Optional
Rear Window	Standard
Top Window	Standard
Seat Belt	Standard 2-Point Lap Belt and Optional 3-Point Shoulder Belt on Two-Speed Models
Spark Arrestor Muffler	DOC

Lift-Arm Support	Standard
------------------	----------

T66 Features & Benefits

Expand all ▾

Performance 16	▾
Uptime Protection 7	▾
Comfort 9	▾
Serviceability 5	▾
Versatility 3	▾

T66 Attachments

[View All Attachments >](#)

 Bob-Tach Mounted Backhoe Turn your loader into a powerful excavator with the powerful digging force of the Bob-Tach® backhoe attachment.	 Brushcat - 66", High Flow Clear trails or construction sites.	 Brushcat - 66", Standard Flow Clear trails or construction sites.
--	---	--



WARNING: This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.